

 **Flavy FX 2 / 3**



Flavy FX 3

The range of Flavy FX2 and FX3 filters is the best answer to small wineries requirements.

- Respect of the wine organoleptic quality as structure, color, aromas...
- Minimal wine losses thanks to the inert gas “pushing process” at the end of filtration.
- Decrease of the wine oxidation thanks to the absence of oxygen in the filter unit.
- Fully automatic filtration process.
- Optimized price per gallon, or per liter.
- Dead volumes designed to reduce wine losses and water consumption.



Flavy FX 3

Technical characteristics

Model Flavy	Number of modules	Filtration surface (m ²)	Length (mm)	Height (mm)	Width (mm)	Empty weight (kg)	Power (kW)
FX 2	2	24	1568	861	1834	325	4.75
FX 3	3	36	1836	861	1834	400	8.6

Flavy FX 2 and 3 models are delivered with a washing products distributor.

Fitting dimensions

- Wine in / out: DIN 40.
- Retentate and back flush output: DIN 40.
- Water fitting: F 1" Gaz.
- Air / Nitrogen fittings: 10 bar, F ¼" Gaz.
- Equipression fittings: F ¾" Gaz.

Average flows obtained during trials

Wines	Flavy FX 2	Flavy FX 3
Dry white wine*	16 - 24 hl/h	24 - 36 hl/h
Gross rose wine*	14 hl/h	21 hl/h
Red wine*	8 - 14 hl/h	12 - 21 hl/h

*Results for information only – to be confirmed

Options

- Turbidimeter.
- Water prefilters (5µm and 1µm).
- Sparkling wines.
- In-line UF bentonite injection.
- Conductivity probe.
- Tank management with 3 input valves and 3 output valves.
- Automatic resumption of external tank.

Distributed by :

Bucher Vaslin
Rue Gaston Bernier – BP 70028
F - 49290 Chalonnes sur Loire
Tél. +33 (0)2 41 74 50 50
Fax +33 (0)2 41 74 50 51
E-mail : commercial@buchervaslin.com

www.buchervaslin.com
Your success is our priority