

# TailGator<sup>™</sup> Depalletizer



Cans - 8oz - 19.2oz



Increase Operator Safety



**Small Footprint** 



**Reduce Manual Labor** 



**Stainless Steel** 



## **Semi-Automatic Excellence**

A.B.E.'s TailGator<sup>™</sup> Semi-automatic empty can depalletizer attaches directly to A.B.E.'s CraftCan<sup>™</sup> series canning lines. Cans are loaded onto the stainless steel loading table where they await elevation to create a downward flow of cans to the output of the unit. After an entire "slip" of cans is placed onto the loading table, a manual switch is engaged to lift the back-end of the table, which causes the cans to feed into the output, with assistance from an automated vibrating motor. Once elevated, cans smoothly and easily slide into position in preparation for delivery to an in-line twist rinse or directly onto the canning line.

(402) 475-2337



AmericanBeerEquipment.com



## **TailGator<sup>™</sup> Depalletizer**

### **FEATURES**

- · 65 cans per minute continuous operation
- Allows for a full slip of cans to be placed on the staging area of the depalletizer
- Compatible with a wide variety of cans
- Tilts and vibrates to allow for feeding into twist rinse
- · Actuated by pneumatic lift cylinders
- Stainless steel construction
- Standard conveyor height and elevated options available for adding an in-line twist rinse
- Adjustable leg height to allow for direct can feed onto canning line and elevated to allow for an in-line twist to canning line
- · Compact, sturdy design for long operating life
- · Adjustable feet that can be bolted to the floor
- Height adjustment from 8oz to 16 oz (metric sizes also)
- Meets CSA / UL and EU standards
- Simple to install and maintain a minimum number electrical and product hookups
- Capable of handling foaming detergent for cleaning of system
  exterior

### Optional can twist rinser that feeds onto canning line

Note: A.B.E. reserves the right to change specifications without prior notification all specifications are approximate ±10%

Non-Elevated Dimensions:

- Length: 106 in (269.3 cm)
- Width: 50 in (127 cm)
- Height: 60 in (152.4 cm)

Elevated Dimensions:

- Length: 106 in (269.3 cm)
- Width: 50 in (127 cm)
- Height: 101 in (256.6 cm)

#### Electrical Requirements:

- 110, 1-phase, 50 / 60 Hz.
- Other electrical options available

Air Requirement: 90 PSI @ 1 CFM



(402) 475-2337 AmericanBeerEquipment.com